

Accessories

Power Supplies

DR-4524

45W, 24 VDC, 0~2A DIN-Rail Power Supply, Input: 85~264VAC; 120~370VDC



Input:
85~264VAC; 120~370VDC
Output:
45W, 24 VDC, 0-2A
AC inrush current:
30A at 115VAC, 60A at 230VAC
Over load protection:
105%~150%
Over voltage protection:
115~135% of rated output voltage
Type:
Constant Current Limiting
Reset:
Auto Recovery

Operating Temperature:
-10~50°C
Operating Humidity:
20~90% RH
Safety standards:
UL508, TUV EN60950-1
EMC standards:
EN55022 class B, EN61000-3-2,3,
EN61000-6-2, EN61000-4-
2,3,4,5,6,8,11
ENV50204
Weight:
0.31 kg
Dimensions:
78(W) x 93(H) x 67(D)mm

DR-75-24

75W, 24 VDC, 0~3.2A DIN-Rail Power Supply, Input: 85~264VAC; 120~370VDC



Input:
85~264 VAC; 120~370VDC
Output:
75W, 24 VDC, 0-3.2A
AC inrush current:
30A at 115VAC, 60A at 230VAC
Over load protection:
105%~150%
Over voltage protection:
121~142% of rated output voltage
Type:
Constant Current Limiting
Reset:
Auto Recovery

Operating Temperature:
-10~60°C
Operating Humidity:
20~90% RH
Safety standards:
UL508, TUV EN60950-1 approved
EMC standards:
EN55022 class B, EN61000-3-2,3,
EN61000-6-2, EN61000-4-
2,3,4,5,6,8,11
ENV50204
Weight:
0.6 kg
Dimensions:
55.5(W) x 125.2(H) x 100(D)mm

DR-120-24

120W, 24 VDC, 0~5A DIN-Rail Power Supply, Input: 88~132VAC/ 176~264VAC



Input:
88~132 VAC/ 176~264VAC
selectable by switch
Output:
120W, 24 VDC, 0-5A
AC inrush current:
30A at 115VAC, 60A at 230VAC
Over load protection:
105%~150%
Over voltage protection:
120~140% of rated output voltage
Type:
Constant Current Limiting
Reset:
Auto Recovery

Operating Temperature:
-10~60°C
Operating Humidity:
20~90% RH
Safety standards:
UL508, UL60950-1, TUV EN60950-1
approved
EMC standards:
EN55022 class B, EN61000-3-2,3,
EN61000-6-2, EN61000-4-
2,3,4,5,6,8,11,
ENV50204
Weight:
0.79 kg
Dimensions:
65.5(W) x 125.2(H) x 100(D)mm